Long Oil Alkyd Resin 70% (Low Viscosity) $JP-L\ 101$



DESCRIPTION

Based On Soya Bean Oil, Supplied At 70% Non-Volatile In White Spirit.

SPECIFICATIONS:

| Oil Type & Length | Soya Bean Oil 65% |
|--|-----------------------|
| Solid Content | 70 ± 2% |
| Solvent | White Spirit |
| Acid KOH/mg (Max) | 10 |
| Viscosity at 25 C in 50% solid Poise (Max) | 3 |
| Color on Gardner Scale 70% Solution of Resin (Max) | 4 |
| Hydroxyl No. | 59 |

PRINCIPLE PROPERTIES:

- High resistance to yellowing.
- Excellent Adhesion.
- Excellent Surface & Deep Drying.
- Good Pigment Wetting & Dispersing.
- Very Good Solvent Acceptation.

APPLICATIONS:

Gloss, semi-gloss architectural paints. Architectural & industrial varnishes, metal structural coatings, Wood & metal coatings, & very good yellowing resistance.

PACKAGING:

Steel Drums 190 Kg Net.

STORAGE AND STABILITY:

This product must be stored in its (original, recondition) sealed plastic drum, in a dry place away from fire, heat source, spark and direct sunlight in temperatures between 5-30 \mathcal{C} .

Under these conditions, the shelf life will be 2 Years from Production date.