

# Short Alkyd Resin 60% (Fast Drying) JP –SH 302



## DESCRIPTION

Fast -Drying Short Oil Alkyd Resin based on Soya Bean Oil, supplied at 60% Non-Volatile in Xylene.

## SPECIFICATIONS:

Oil Type & Length	.....	Soya Bean Oil 35%
Solid Content	.....	60 ± 2%
Solvent	.....	Xylene
Acid KOH/mg (Max)	.....	12
Viscosity at 25 C° in 50% solid Poise (Max)	.....	7
Color on Gardner Scale 70% Solution of Resin (Max)	.....	6

## PRINCIPLE PROPERTIES:

- High resistance to yellowing.
- Higher viscosity chain stopped.
- Excellent salt spray resistance.
- Extremely fast dry like styrenated Alkyd.
- Compatible with chlorinated rubber.
- 

## APPLICATIONS:

Isolating Varnish, corrosion resistance primers air drying and stoving finishes, traffic paints.

## PACKAGING:

Steel Drums 190 Kg Net.

## STORAGE AND STABILITY:

This product must be stored in its (original, recondition) sealed plastic drum, in a dry place away from fire, heat source, spark and direct sunlight in temperatures between 5-30 C°.

Under these conditions, the shelf life will be 2 years from Production date.